

RG 213 /U



Application

Used in high frequency transmission, especially for transmitters and receivers, computers, radio and TV transmissions. The varied mechanical, thermal and electronic properties of coaxial cables allow the use to GHz levels according to the cable type.

The materials used are free from silicon and cadmium and free from varnish damaging sustances.

Standards

US-Military specifications MIL-C-17

Construction

Inner Conductor	7 x 0,75 copper, bare
Core Insulation	7,24 PE
Overall Shielding	bare, copper braid
Outer Insulation Material	special polyvinylchlorid (PVC)

Technical Data

Nominal Voltage	U ₀ /U: 0 /0
Nominal Volatage DC	U ₀ /U: 0 /0
Bending Radius fixed (xD)	0
Operating Temperature solid	-35 °C bis 80 °C
Operating Temperature moving	0 °C bis 0 °C

Application

Used in high frequency transmission, especially for transmitters and receivers, computers, radio and TV transmissions. The varied mechanical, thermal and electronic properties of coaxial cables allow the use to GHz levels according to the cable type.

The materials used are free from silicon and cadmium and free from varnish damaging sustances.

Standards

US-Military specifications MIL-C-17

Construction

Inner Conductor	7 x 0,75 copper, bare
Core Insulation	7,24 PE
Overall Shielding	bare, copper braid
Outer Insulation Material	special polyvinylchlorid (PVC)

Technical Data

Nominal Voltage	U ₀ /U: 0 /0
Nominal Volatage DC	U ₀ /U: 0 /0
Bending Radius fixed (xD)	0
Operating Temperature solid	-35 °C to 80 °C
Operating Temperature moving	0 °C to 0 °C



Prod. Nr.	Dimensions	Color	Weight (kg/km)	Outer-Diameter (mm)
Prod. Nr.	Dimensions	Color	Weight (kg/km)	Outer-Diameter (mm)
03001011	RG x 213 /U	black - black	157.0	10.3