

(N)YM(ST)Y-J



Application

These installation cables are made for an effective range of electromagnetic interference alternating fields by a static screen. This screening is specially used for the installation in computer sector, hospitals or industry measuring observation points with measuring instruments which are sensitive to interferences. These cables are also ideal for installations in the living rooms of those peoples who are extreme sensitive to radiation. The cable is suitable for laying on, in and under plaster in dry and damp places as well as in concrete and masonry (a direct laying in shaken or stamped concrete is excluded). Outdoor laying only is possible if the cable is not exposed to direct sunlight or if the cable is layed in cable conduits. Use in dangerous areas is not allowed.

The materials used are free from silicon and cadmium and free from varnish damaging sustances.

Standards

adapted to DIN VDE 0250 part 204/209,  
self-extinguishing and flame retardant acc. to VDE 0482  
part 265-2-1, EN 50265-2-1, IEC 60332-1

CE = The product is conformed with the EC Low-Voltage  
Directive 2014/35/EU.

Construction

<b>Inner Conductor</b>	solid bare copper conductor to DIN VDE 0295 cl. 1, BS 6360 cl. 1 and IEC 60228 cl. 1
<b>Core Insulation</b>	Polyvinyl chloride (PVC)
<b>Core Color</b>	acc. HD 308 S2
<b>Stranding Elements</b>	cores stranded in layers with optimal lay- length
<b>Shielding</b>	coated aluminium foil screening with tinned drain wire
<b>Outer Insulation Material</b>	Polyvinyl chloride (PVC) TM1, to DIN VDE 0281 part 1

Application

These installation cables are made for an effective range of electromagnetic interference alternating fields by a static screen. This screening is specially used for the installation in computer sector, hospitals or industry measuring observation points with measuring instruments which are sensitive to interferences. These cables are also ideal for installations in the living rooms of those peoples who are extreme sensitive to radiation. The cable is suitable for laying on, in and under plaster in dry and damp places as well as in concrete and masonry (a direct laying in shaken or stamped concrete is excluded). Outdoor laying only is possible if the cable is not exposed to direct sunlight or if the cable is layed in cable conduits. Use in dangerous areas is not allowed.

The materials used are free from silicon and cadmium and free from varnish damaging sustances.

Standards

adapted to DIN VDE 0250 part 204/209,  
self-extinguishing and flame retardant acc. to VDE 0482  
part 265-2-1, EN 50265-2-1, IEC 60332-1

CE = The product is conformed with the EC Low-Voltage  
Directive 2014/35/EU.

Construction

<b>Inner Conductor</b>	solid bare copper conductor to DIN VDE 0295 cl. 1, BS 6360 cl. 1 and IEC 60228 cl. 1
<b>Core Insulation</b>	Polyvinyl chloride (PVC)
<b>Core Color</b>	acc. HD 308 S2
<b>Stranding Elements</b>	cores stranded in layers with optimal lay- length
<b>Shielding</b>	coated aluminium foil screening with tinned drain wire
<b>Outer Insulation Material</b>	Polyvinyl chloride (PVC) TM1, to DIN VDE 0281 part 1



Technical Data

Nominal Voltage	U <sub>0</sub> /U: 300 /500 V
Nominal Volatage DC	U <sub>0</sub> /U: 0 /0
Test Voltage	2000 V
Bending Radius moved (xD)	15
Bending Radius fixed (xD)	7.5
Operating Temperature solid	-30 °C bis 70 °C
Operating Temperature moving	5 °C bis 70 °C
Fire Classes	Eca

Technical Data

Nominal Voltage	U <sub>0</sub> /U: 300 /500 V
Nominal Volatage DC	U <sub>0</sub> /U: 0 /0
Test Voltage	2000 V
Bending Radius moved (xD)	15
Bending Radius fixed (xD)	7.5
Operating Temperature solid	-30 °C to 70 °C
Operating Temperature moving	5 °C to 70 °C
Fire Classes	Eca

Prod. Nr. Prod. Nr.	Dimensions Dimensions	Color Color	Weight (kg/km) Weight (kg/km)	Outer-Diameter (mm) Outer-Diameter (mm)	Calorific potential (kWh/m) Calorific potential (kWh/m)
00202001	3 x 1,5/1,5	grey - grey	174.0	10.5	0.44
00202005	3 x 2,5/1,5	grey - grey	217.0	12.0	0.58
00202010	3 x 4/1,5	grey - grey	228.0	13.5	
00202011	3 x 6/1,5	grey - grey	378.0	15.0	
00202002	4 x 1,5/1,5	grey - grey	184.0	11.5	0.53
00202012	4 x 2,5/1,5	grey - grey	256.0	13.0	
00202003	5 x 1,5/1,5	grey - grey	228.0	12.0	0.58
00202006	5 x 2,5/1,5	grey - grey	296.0	13.5	0.75
00202007	5 x 4/1,5	grey - grey	439.0	16.5	
00202009	5 x 6/1,5	grey - grey	565.0	17.5	
00202008	5 x 10/1,5	grey - grey	840.0	21.5	
00202004	7 x 1,5/1,5	grey - grey	263.0	13.0	0.67