

LSZ-XY HF



Application

As high flexible connecting cable in speaker systems.

The materials used are free from silicon and cadmium and free from varnish damaging sustances.

Standards

acc. to factory standard,
self-extinguishing and flame retardant acc. to DIN EN 60332-1-2, IEC 60332-1

Construction

Inner Conductor fine-stranded bare copper acc. DIN VDE 0295 cl. 6 / IEC 60228 cl. 6

Core Insulation special polyvinylchlorid compound (PVC)

Stranding Elements cores parallel

Technical Data

Nominal Voltage	U ₀ /U: 200 /300 V
Nominal Volatage DC	U ₀ /U: 0 /0
Bending Radius moved (xD)	8
Bending Radius fixed (xD)	0
Operating Temperature solid	0 °C bis 0 °C
Operating Temperature moving	-5 °C bis 70 °C

Application

As high flexible connecting cable in speaker systems.

The materials used are free from silicon and cadmium and free from varnish damaging sustances.

Standards

acc. to factory standard,
self-extinguishing and flame retardant acc. to DIN EN 60332-1-2, IEC 60332-1

Construction

Inner Conductor fine-stranded bare copper acc. DIN VDE 0295 cl. 6 / IEC 60228 cl. 6

Core Insulation special polyvinylchlorid compound (PVC)

Stranding Elements cores parallel

Technical Data

Nominal Voltage	U ₀ /U: 200 /300 V
Nominal Volatage DC	U ₀ /U: 0 /0
Bending Radius moved (xD)	8
Bending Radius fixed (xD)	0
Operating Temperature solid	0 °C to 0 °C
Operating Temperature moving	-5 °C to 70 °C

Prod. Nr. Prod. Nr.	Dimensions Dimensions	Color Color	Weight (kg/km) Weight (kg/km)	Outer-Diameter (mm) Outer-Diameter (mm)
00317001	2 x 1,5	transparent/red - transparent/red	41.0	4.0
00317014	2 x 1,5	black/red - black/red	41.0	4.0
00317002	2 x 2,5	transparent/red - transparent/red	61.0	6.0
00317012	2 x 2,5	black/red - black/red	61.0	6.0
00317003	2 x 4	transparentně - transparent	104.0	8.0
00317004	2 x 6	transparentně - transparent	156.0	10.0