RG 62 A/U



Application

Used in high frequency transmission, especially for transmitters and receivers, computers, radio and TV transmissions. The varied mechanical, thermal and electronic properties of coaxial cables allow the use to GHz levels according to the cable type.

The materials used are free from silicon and cadmium and free from varnish damaging sustances.

Standards

US-Military specifications MIL-C-17

Construction

Inner Conductor	1 x 0,65 Steel/copper, bare
Core Insulation	3,7 PE, hollow
Overall Shielding	bare, copper braid
Outer Insulation Material	special polyvinylchlorid (PVC)

Technical Data

Nominal Voltage	U_0/U: 0 /0
Nominal Volatage DC	U_0/U: 0 /0
Bending Radius fixed (xD)	0
Operating Temperature solid	-20 °C bis 70 °C
Operating Temperature moving	0 °C bis 0 °C

Application

Used in high frequency transmission, especially for transmitters and receivers, computers, radio and TV transmissions. The varied mechanical, thermal and electronic properties of coaxial cables allow the use to GHz levels according to the cable type.

The materials used are free from silicon and cadmium and free from varnish damaging sustances.

Standards

US-Military specifications MIL-C-17

Construction

Inner Conductor	1 x 0,65 Steel/copper, bare
Core Insulation	3,7 PE, hollow
Overall Shielding	bare, copper braid
Outer Insulation Material	special polyvinylchlorid (PVC)

Technical Data

Nominal Voltage	U_0/U: 0 /0
Nominal Volatage DC	U_0/U: 0 /0
Bending Radius fixed (xD)	0
Operating Temperature solid	-20 °C to 70 °C
Operating Temperature moving	0 °C to 0 °C

ACS Handels GmbH
Kabel - Leitungen - Zubehör
Bahnhofstraße 1, 4531 Kematen / Krems

Tel.: +43 7228 200 880
E-Mail: office@acs.at

Technische Änderungen und Druckfehler vorbehalten
Technical changes and printing errors reserved

Produktabbildungen sind Symbolfotos
Product images are symbolic photos

Copyright© ACS Handels GmbH

RG und Koaxialkabel
Coaxial Cables

Prod. Nr. Prod. Nr.	Dimensions Dimensions	Color Color	Weight (kg/km) approx. Weight (kg/km) approx.	Outer-Diameter (mm) approx. Outer-Diameter (mm) approx.
03001007	RG x 62 A/U	black - black	55,0	6,2

ACS Handels GmbH
Kabel - Leitungen - Zubehör
Bahnhofstraße 1, 4531 Kematen / Krems

Tel.: +43 7228 200 880
E-Mail: office@acs.at

Technische Änderungen und Druckfehler vorbehalten
Technical changes and printing errors reserved

Produktabbildungen sind Symbolfotos
Product images are symbolic photos

Copyright© ACS Handels GmbH