

## H07VVH6-F



### Application

PVC type of flat cables are used mainly as trailing cable for crane installations, floor conveyer systems and shelf control units. Suitable for dry, humid and wet rooms and for outdoor use.

The materials used are free from silicon and cadmium and free from varnish damaging substances.

### Standards

to DIN EN 50214 VDE 0283-2:2007-10,  
EN 60332-1-2, IEC 60332-1

CE = The product is conformed with the EC Low-Voltage Directive 2014/35/EU.

### Construction

**Inner Conductor** fine-stranded bare copper acc. DIN  
VDE 0295 cl. 5 / IEC 60228 cl. 5

**Core Insulation** special polyvinylchlorid compound  
(PVC)

**Core Color** acc. to DIN VDE 0293 respectively HD  
308 S2, 7 cores black with continuous  
white numbers printed

**Outer Insulation Material** special PVC

**Constant Against** ozone and UV radiation

### Technical Data

<b>Nominal Voltage</b>	$U_0/U$ : 450 /750 V
<b>Nominal Volatage DC</b>	$U_0/U$ : 0 /0
<b>Test Voltage</b>	2500 V
<b>Bending Radius moved (xD)</b>	5
<b>Bending Radius fixed (xD)</b>	0
<b>Operating Temperature solid</b>	-40 °C bis 80 °C
<b>Operating Temperature moving</b>	-5 °C bis 70 °C
<b>Short Circuit Temperature</b>	150 °C
<b>Short Circuit Duration</b>	5 sek.

### Application

PVC type of flat cables are used mainly as trailing cable for crane installations, floor conveyer systems and shelf control units. Suitable for dry, humid and wet rooms and for outdoor use.

The materials used are free from silicon and cadmium and free from varnish damaging substances.

### Standards

to DIN EN 50214 VDE 0283-2:2007-10,  
EN 60332-1-2, IEC 60332-1

CE = The product is conformed with the EC Low-Voltage Directive 2014/35/EU.

### Construction

**Inner Conductor** fine-stranded bare copper acc.  
DIN  
VDE 0295 cl. 5 / IEC 60228 cl. 5

**Core Insulation** special polyvinylchlorid compound  
(PVC)

**Core Color** acc. to DIN VDE 0293 respectively HD  
308 S2, 7 cores black with continuous  
white numbers printed

**Outer Insulation Material** special PVC

**Constant Against** ozone and UV radiation

### Technical Data

<b>Nominal Voltage</b>	$U_0/U$ : 450 /750 V
<b>Nominal Volatage DC</b>	$U_0/U$ : 0 /0
<b>Test Voltage</b>	2500 V
<b>Bending Radius moved (xD)</b>	5
<b>Bending Radius fixed (xD)</b>	0
<b>Operating Temperature solid</b>	-40 °C to 80 °C
<b>Operating Temperature moving</b>	-5 °C to 70 °C
<b>Short Circuit Temperature</b>	150 °C
<b>Short Circuit Duration</b>	5 sek.

Prod. Nr.	Option	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.
Prod. Nr.	Option	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.
00607010	5,4 x 15,0	4 G 1,5	black - black	150,0	
00607016	6,7 x 19,0	4 G 2,5	black - black	215,0	
00607021	7,2 x 21,5	4 G 4	black - black	320,0	
00607024	8,0 x 23,8	4 G 6	black - black	430,0	
00607026	9,9 x 30,0	4 G 10	black - black	690,0	
00607027	11,0 x 35,0	4 G 16	black - black	970,0	
00607029	13,5 x 43,0	4 G 25	black - black	1.405,0	
00607030	15,0 x 48,0	4 G 35	black - black	2.035,0	
00607031	17,0 x 56,0	4 G 50	black - black	3.000,0	
00607042	20,0 x 66,0	4 G 70	black - black	4.100,0	
00607043	21,0 x 95,0	4 G 95	black - black	4.550,0	
00607011	5,4 x 17,7	5 G 1,5	black - black	180,0	
00607017	6,7 x 21,6	5 G 2,5	black - black	260,0	
00607022	7,2 x 24,0	5 G 4	black - black	390,0	
00607032	8,0 x 28,5	5 G 6	black - black	530,0	
00607044	9,9 x 37,5	5 G 10	black - black	810,0	
00607028	11,0 x 48,0	5 G 16	black - black	1.170,0	
00607012	5,4 x 26,2	7 G 1,5	black - black	265,0	
00607018	6,7 x 32,0	7 G 2,5	black - black	385,0	
00607023	7,2 x 35,7	7 G 4	black - black	550,0	
00607025	8,0 x 40,0	7 G 6	black - black	750,0	
00607013	5,4 x 28,5	8 G 1,5	black - black	295,0	
00607019	6,7 x 35,0	8 G 2,5	black - black	430,0	
00607014	5,4 x 35,8	10 G 1,5	black - black	355,0	

# Flachleitungen

## Flat Cables Rubber/PVC/LSOH



Prod. Nr.	Option	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.
Prod. Nr.	Option	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.
00607015	5,4 x 42,5	12 G 1,5	black - black	415,0	
00607020	6,7 x 49,5	12 G 2,5	black - black	610,0	
00607080	5,4 x 52,5	14 G 1,5	black - black	480,0	
00607050	5,4 x 57,0	16 G 1,5	black - black	555,0	
00607036	5,4 x 62,0	18 G 1,5	black - black	710,0	
00607041	5,4 x 83,0	24 G 1,5	black - black	790,0	
00607048	6,7 x 100,0	24 G 2,5	black - black	950,0	

**ACS Handels GmbH**  
**Kabel - Leitungen - Zubehör**  
Bahnhofstraße 1, 4531 Kematen / Krems

Tel.: +43 7228 200 880  
E-Mail: office@acs.at

Technische Änderungen und Druckfehler vorbehalten  
Technical changes and printing errors reserved

Produktabbildungen sind Symbolfotos  
Product images are symbolic photos

Copyright© ACS Handels GmbH