

DataFlex S/FTP 600 MHz Cat7



Application

Contributes to the transmission of analogue and digital signals wiring in the working and switching area in the Frequency range up to 600MHz.

Suitable for applications up to Class F (600MHz).

IEEE 802.3 : Ethernet 10Base-T ; Fast Ethernet 100Base-T ; Gigabit Ethernet 1000Base-T ; 10GBase-T IEEE 802.5 : ISDN ; FDDI ; ATM ; Cable sharing
IEEE 802.3at : PoE suitable

Standards

EN 50288-4-2 ; EN 50173 ; EN 50174-2 ;
ISO/IEC 11801 2nd edition ; IEC 61156-6

Construction

Inner Conductor copper stranned, tinned, AWG 26/7
Core Insulation SFS-PE
Core Color acc. IEC 708-1
Shielding pairs shielded with aluminum foil
Overall Shielding Tinned copper braid, 0,10mm
Outer Insulation Material halogen free compound (FRNC)

Technical Data

Nominal Voltage	U ₀ /U: 125 /125 V
Nominal Volatage DC	U ₀ /U: 0 /0
Test Voltage	700 V
Bending Radius moved (xD)	8
Bending Radius fixed (xD)	4
Operating Temperature solid	-20 °C bis 60 °C
Operating Temperature moving	0 °C bis 50 °C

Application

Contributes to the transmission of analogue and digital signals wiring in the working and switching area in the Frequency range up to 600MHz.

Suitable for applications up to Class F (600MHz).

IEEE 802.3 : Ethernet 10Base-T ; Fast Ethernet 100Base-T ; Gigabit Ethernet 1000Base-T ; 10GBase-T IEEE 802.5 : ISDN ; FDDI ; ATM ; Cable sharing
IEEE 802.3at : PoE suitable

Standards

EN 50288-4-2 ; EN 50173 ; EN 50174-2 ;
ISO/IEC 11801 2nd edition ; IEC 61156-6

Construction

Inner Conductor copper stranned, tinned, AWG 26/7
Core Insulation SFS-PE
Core Color acc. IEC 708-1
Shielding pairs shielded with aluminum foil
Overall Shielding Tinned copper braid, 0,10mm
Outer Insulation Material halogen free compound (FRNC)

Technical Data

Nominal Voltage	U ₀ /U: 125 /125 V
Nominal Volatage DC	U ₀ /U: 0 /0
Test Voltage	700 V
Bending Radius moved (xD)	8
Bending Radius fixed (xD)	4
Operating Temperature solid	-20 °C to 60 °C
Operating Temperature moving	0 °C to 50 °C

Datenkabel Kategorie 5-7

Computer Cables Cat. 5-7



Prod. Nr.	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.
Prod. Nr.	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.
03431002	4x2 x AWG 26/7	grey - grey	42,0	5,9
03431008	4x2 x AWG 26/7	yellow - yellow	42,0	5,9

ACS Handels GmbH
Kabel - Leitungen - Zubehör
Bahnhofstraße 1, 4531 Kematen / Krems

Tel.: +43 7228 200 880
E-Mail: office@acs.at

Technische Änderungen und Druckfehler vorbehalten
Technical changes and printing errors reserved

Produktabbildungen sind Symbolfotos
Product images are symbolic photos

Copyright© ACS Handels GmbH