

## Cu-rope



### Application

For connecting to ground in power installations.

### Standards

Soft type: IEC 60228 class 2

Hard type: DIN 48201/1

CE = The product is conformed with the EC Low-Voltage Directive 2014/35/EU.

### Construction

**Inner Conductor** copper wire stranded, bare or tinned

### Technical Data

**Nominal Voltage**  $U_0/U$ : 0 /0

**Nominal Volatage DC**  $U_0/U$ : 0 /0

**Bending Radius fixed (xD)** 0

**Operating Temperature solid** 0 °C bis 0 °C

**Operating Temperature moving** 0 °C bis 0 °C

### Application

For connecting to ground in power installations.

### Standards

Soft type: IEC 60228 class 2

Hard type: DIN 48201/1

CE = The product is conformed with the EC Low-Voltage Directive 2014/35/EU.

### Construction

**Inner Conductor** copper wire stranded, bare or tinned

### Technical Data

**Nominal Voltage**  $U_0/U$ : 0 /0

**Nominal Volatage DC**  $U_0/U$ : 0 /0

**Bending Radius fixed (xD)** 0

**Operating Temperature solid** 0 °C to 0 °C

**Operating Temperature moving** 0 °C to 0 °C

Prod. Nr.	Option	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.
Prod. Nr.	Option	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.
04101020	blank 7	1 x 10 blank,weich		90,0	4,0
04101021	verzinnt 7	1 x 10 verzinnt,weich		90,0	4,0
04101001	blank 7	1 x 16 blank,weich		143,0	5,2
04101010	verzinnt 7	1 x 16 verzinnt,weich		143,0	5,2
04101007	blank 7	1 x 25 blank,weich		230,0	6,4
04101012	verzinnt 7	1 x 25 verzinnt,weich		230,0	6,4
04101002	blank 7	1 x 35 blank,weich		310,0	7,6
04101013	verzinnt 7	1 x 35 verzinnt,weich		310,0	7,6
04101018	blank 19	1 x 50 blank,weich		446,0	8,9
04101014	verzinnt 19	1 x 50 verzinnt,weich		446,0	8,9
04101004	blank 19	1 x 70 blank,weich		610,0	10,6
04101009	verzinnt 19	1 x 70 verzinnt,weich		610,0	10,6
04101005	blank 19	1 x 95 blank,weich		912,0	12,7
04101015	verzinnt 19	1 x 95 verzinnt,weich		912,0	12,7
04101043	37	1 x 120 blank,weich		1.060,0	14,3
04101044	blank 19	1 x 120 blank,weich		1.060,0	14,3
04101016	verzinnt 19	1 x 120 verzinnt,weich		1.060,0	14,3
04101026	blank 37	1 x 150 blank,weich		1.300,0	15,3
04101049	verzinnt 37	1 x 150 verzinnt,weich		1.300,0	15,3
04101008	blank 37	1 x 185 blank,weich		1.640,0	17,7
04101017	verzinnt 37	1 x 185 verzinnt,weich		1.640,0	17,7
04101022	blank 37	1 x 240 blank,weich		2.133,0	20,5
04101027	blank 37	1 x 300 blank,weich		2.791,0	22,6