Cu-rope



Application

For connecting to ground in power installations.

Standards

Soft type: IEC 60228 class 2
Hard type: DIN 48201/1

CE = The product is conformed with the EC Low-Voltage Directive 2014/35/EU.

Construction

Inner Conductor copper wire stranded, bare or tinned

Technical Data

Nominal Voltage	U_0/U: 0 /0
Nominal Volatage DC	U_0/U: 0 /0
Bending Radius fixed (xD)	0
Operating Temperature solid	0 °C bis 0 °C
Operating Temperature moving	0 °C bis 0 °C

Application

For connecting to ground in power installations.

Standards

Soft type: IEC 60228 class 2
Hard type: DIN 48201/1

CE = The product is conformed with the EC Low-Voltage Directive 2014/35/EU.

Construction

Inner Conductor copper wire stranded, bare or tinned

Technical Data

Nominal Voltage	U_0/U: 0 /0
Nominal Volatage DC	U_0/U: 0 /0
Bending Radius fixed (xD)	0
Operating Temperature solid	0 °C to 0 °C
Operating Temperature moving	0 °C to 0 °C

ACS Handels GmbH
Kabel - Leitungen - Zubehör
Bahnhofstraße 1, 4531 Kematen / Krems

Tel.: +43 7228 200 880
E-Mail: office@acs.at

Technische Änderungen und Druckfehler vorbehalten
Technical changes and printing errors reserved

Produktabbildungen sind Symbolfotos
Product images are symbolic photos

Copyright© ACS Handels GmbH

Cu/Alu/Stahlseile/Drähte
Copper / Aluminium / Steel rope

Prod. Nr. Prod. Nr.	Option Option	Dimensions Dimensions	Color Color	Weight (kg/km) approx. Weight (kg/km) approx.	Outer-Diameter (mm) approx. Outer-Diameter (mm) approx.
04101020	blank 7	1 x 10 blank,weich		90,0	4,0
04101021	verzinnt 7	1 x 10 verzinnt,weich		90,0	4,0
04101001	blank 7	1 x 16 blank,weich		143,0	5,2
04101010	verzinnt 7	1 x 16 verzinnt,weich		143,0	5,2
04101007	blank 7	1 x 25 blank,weich		230,0	6,4
04101012	verzinnt 7	1 x 25 verzinnt,weich		230,0	6,4
04101002	blank 7	1 x 35 blank,weich		310,0	7,6
04101013	verzinnt 7	1 x 35 verzinnt,weich		310,0	7,6
04101018	blank 19	1 x 50 blank,weich		446,0	8,9
04101014	verzinnt 19	1 x 50 verzinnt,weich		446,0	8,9
04101004	blank 19	1 x 70 blank,weich		610,0	10,6
04101009	verzinnt 19	1 x 70 verzinnt,weich		610,0	10,6
04101005	blank 19	1 x 95 blank,weich		912,0	12,7
04101015	verzinnt 19	1 x 95 verzinnt,weich		912,0	12,7
04101043	37	1 x 120 blank,weich		1.060,0	14,3
04101044	blank 19	1 x 120 blank,weich		1.060,0	14,3
04101016	verzinnt 19	1 x 120 verzinnt,weich		1.060,0	14,3
04101026	blank 37	1 x 150 blank,weich		1.300,0	15,3
04101049	verzinnt 37	1 x 150 verzinnt,weich		1.300,0	15,3
04101008	blank 37	1 x 185 blank,weich		1.640,0	17,7
04101017	verzinnt 37	1 x 185 verzinnt,weich		1.640,0	17,7
04101022	blank 37	1 x 240 blank,weich		2.133,0	20,5
04101027	blank 37	1 x 300 blank,weich		2.791,0	22,6

ACS Handels GmbH
Kabel - Leitungen - Zubehör
Bahnhofstraße 1, 4531 Kematen / Krems

Tel.: +43 7228 200 880
E-Mail: office@acs.at

Technische Änderungen und Druckfehler vorbehalten
Technical changes and printing errors reserved

Produktabbildungen sind Symbolfotos
Product images are symbolic photos

Copyright© ACS Handels GmbH