

## N2XSEY

### Application

For laying indoors, in cable ducts, in ground, as well for laying on racks for industrial and switching systems and power stations. Restricted use when laying in the ground if the PVC outer sheath can be damaged as a result of strong mechanical stress.

The materials used are free from silicon and cadmium and free from varnish damaging substances.

### Standards

DIN VDE 0276 part 620,  
flame retardant acc. to VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1

CE = The product is conformed with the EC Low-Voltage Directive 2014/35/EU.

### Construction

<b>Inner Conductor</b>	stranded copper conductor
<b>Core</b>	conductor screen of semi-conducting - XLPE
<b>Insulation</b>	insulation - core - screen of semi-conducting compound
<b>Shielding</b>	copper wire screen applied over each individual core
<b>Inner Sheath Material</b>	inner covering
<b>Outer Insulation Material</b>	Polyvinyl chloride (PVC), red

### Technical Data

<b>Nominal Voltage</b>	$U_0/U$ : 6 /10 kV
<b>Nominal Volatage DC</b>	$U_0/U$ : 0 /0
<b>Test Voltage</b>	15 kV
<b>Bending Radius fixed (xD)</b>	15
<b>Operating Temperature solid</b>	-20 °C bis 80 °C
<b>Operating Temperature moving</b>	-5 °C bis 70 °C
<b>Short Circuit Temperature</b>	160 °C
<b>Short Circuit Duration</b>	5 sek.



### Application

For laying indoors, in cable ducts, in ground, as well for laying on racks for industrial and switching systems and power stations. Restricted use when laying in the ground if the PVC outer sheath can be damaged as a result of strong mechanical stress.

The materials used are free from silicon and cadmium and free from varnish damaging substances.

### Standards

DIN VDE 0276 part 620,  
flame retardant acc. to VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1

CE = The product is conformed with the EC Low-Voltage Directive 2014/35/EU.

### Construction

<b>Inner Conductor</b>	stranded copper conductor
<b>Core</b>	conductor screen of semi-conducting - XLPE
<b>Insulation</b>	insulation - core - screen of semi-conducting compound
<b>Shielding</b>	copper wire screen applied over each individual core
<b>Inner Sheath Material</b>	inner covering
<b>Outer Insulation Material</b>	Polyvinyl chloride (PVC), red

### Technical Data

<b>Nominal Voltage</b>	$U_0/U$ : 6 /10 kV
<b>Nominal Volatage DC</b>	$U_0/U$ : 0 /0
<b>Test Voltage</b>	15 kV
<b>Bending Radius fixed (xD)</b>	15
<b>Operating Temperature solid</b>	-20 °C to 80 °C
<b>Operating Temperature moving</b>	-5 °C to 70 °C
<b>Short Circuit Temperature</b>	160 °C
<b>Short Circuit Duration</b>	5 sek.

# Starkstromkabel 6/10 kV Power Cables 6/10 kV



Prod. Nr. Prod. Nr.	Dimensions Dimensions	Color Color	Weight (kg/km) approx. Weight (kg/km) approx.	Outer-Diameter (mm) approx. Outer-Diameter (mm) approx.
01502009	3 x 25 rm/16	red - red	2.100,0	45,0
01502008	3 x 35 rm/16	red - red	2.600,0	49,0
01502001	3 x 50 rm/16	red - red	2.900,0	51,0
01502002	3 x 70 rm/16	red - red	3.350,0	55,0
01502003	3 x 95 rm/16	red - red	4.200,0	58,0
01502004	3 x 120 rm/16	red - red	5.050,0	62,0
01502005	3 x 150 rm/25	red - red	6.000,0	66,0
01502006	3 x 185 rm/25	red - red	7.200,0	69,0
01502007	3 x 240 rm/25	red - red	10.500,0	71,2
01502010	3 x 300 rm/25	red - red	14.450,0	79,0

**ACS Handels GmbH**  
**Kabel - Leitungen - Zubehör**  
Bahnhofstraße 1, 4531 Kematen / Krems

Tel.: +43 7228 200 880  
E-Mail: office@acs.at

Technische Änderungen und Druckfehler vorbehalten  
Technical changes and printing errors reserved

Produktabbildungen sind Symbolfotos  
Product images are symbolic photos

Copyright© ACS Handels GmbH