

E-YY-J



Application

Power cables for energy supply are installed in open air, in underground, in water, indoors, in cable ducts, power stations, for industry and distribution boards as well as in subscriber networks, where mechanical damages are not to be expected.

The materials used are free from silicon and cadmium and free from varnish damaging substances.

Standards

ÖVE K 23 and K 603,
flame retardant acc. to VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1

CE = The product is conformed with the EC Low-Voltage Directive 2014/35/EU.

Construction

Inner Conductor bare copper conductor solid or stranded, to DIN VDE 0295 cl. 1 or cl. 2, BS 6360 cl. 1 or cl. 2 and IEC 60228 cl. 1 or cl. 2

Core Insulation Polyvinyl chloride (PVC)

Core Color HD 308 S2, (7 cores black with continuous white numbers printed)

Stranding Elements multi cores stranded in layers

Inner Sheath Material filler sheath or tape

Outer Insulation Material Polyvinyl chloride (PVC), black

Constant Against UV-radiation

Application

Power cables for energy supply are installed in open air, in underground, in water, indoors, in cable ducts, power stations, for industry and distribution boards as well as in subscriber networks, where mechanical damages are not to be expected.

The materials used are free from silicon and cadmium and free from varnish damaging substances.

Standards

ÖVE K 23 and K 603,
flame retardant acc. to VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1

CE = The product is conformed with the EC Low-Voltage Directive 2014/35/EU.

Construction

Inner Conductor bare copper conductor solid or stranded, to DIN VDE 0295 cl. 1 or cl. 2, BS 6360 cl. 1 or cl. 2 and IEC 60228 cl. 1 or cl. 2

Core Insulation Polyvinyl chloride (PVC)

Core Color HD 308 S2, (7 cores black with continuous white numbers printed)

Stranding Elements multi cores stranded in layers

Inner Sheath Material filler sheath or tape

Outer Insulation Material Polyvinyl chloride (PVC), black

Constant Against UV-radiation

Energiekabel 1kV

Power Cables copper 1 kV



Technical Data

Nominal Voltage	U ₀ /U: 600 /1000 V
Nominal Volatage DC	U ₀ /U: 900 /1800 V
Test Voltage	4000 V
Bending Radius fixed (xD)	15
Operating Temperature solid	-5 °C bis 70 °C
Operating Temperature moving	-5 °C bis 70 °C
Short Circuit Temperature	160 °C
Short Circuit Duration	5 sek.
Fire Classes	Eca

Technical Data

Nominal Voltage	U ₀ /U: 600 /1000 V
Nominal Volatage DC	U ₀ /U: 900 /1800 V
Test Voltage	4000 V
Bending Radius fixed (xD)	15
Operating Temperature solid	-5 °C to 70 °C
Operating Temperature moving	-5 °C to 70 °C
Short Circuit Temperature	160 °C
Short Circuit Duration	5 sek.
Fire Classes	Eca

ACS Handels GmbH
Kabel - Leitungen - Zubehör
Bahnhofstraße 1, 4531 Kematen / Krems

Tel.: +43 7228 200 880
E-Mail: office@acs.at

Technische Änderungen und Druckfehler vorbehalten
Technical changes and printing errors reserved

Produktabbildungen sind Symbolfotos
Product images are symbolic photos

Copyright© ACS Handels GmbH

Energiekabel 1kV

Power Cables copper 1 kV



Prod. Nr.	Option	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.	Power Load Earth (A)	Power Load Air (A)	Calorific potential (kWh/m)
Prod. Nr.	Option	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.	Power Load Earth (A)	Power Load Air (A)	Calorific potential (kWh/m)
01302215	J	1 x 10 rm	black - black	139,0	8,3	83	67	0,33
01302079	J	1 x 16 re	black - black	219,0	9,0	107	89	0,42
01302080	J	1 x 25 rm	black - black	327,0	11,1	138	119	0,58
01302081	J	1 x 35 rm	black - black	435,0	12,1	164	146	0,67
01302082	J	1 x 50 rm	black - black	576,0	13,7	195	177	0,81
01302083	J	1 x 70 rm	black - black	793,0	15,2	238	221	0,92
01302084	J	1 x 95 rm	black - black	1.069,0	17,2	286	270	1,17
01302085	J	1 x 120 rm	black - black	1.320,0	18,5	325	310	1,31
01302181	J	1 x 150 rm	black - black	1.616,0	22,5	365	350	1,58
01302086	J	1 x 185 rm	black - black	1.995,0	24,6	413	399	1,65
01302087	J	1 x 240 rm	black - black	2.560,0	27,0	479	462	1,77
01302088	J	1 x 300 rm	black - black	3.163,0	30,0	541	519	1,92
01302089	J	3 x 1,5 re	black - black	142,0	9,4	27	20	0,75
01302090	J	3 x 2,5 re	black - black	188,0	10,2	36	25	0,83
01302091	J	3 x 4 re	black - black	267,0	11,8	47	34	1,08
01302092	J	3 x 6 re	black - black	346,0	13,3	59	43	1,22
01302093	J	3 x 10 re	black - black	508,0	15,1	79	59	1,42
01302094	J	3 x 16 re	black - black	734,0	17,5	102	79	1,69
01302095	J	3 x 16 rm	black - black	774,0	17,8	102	79	1,69
01302096	J	3 x 25 rm	black - black	1.188,0	21,5	133	106	2,14

ACS Handels GmbH
Kabel - Leitungen - Zubehör
 Bahnhofstraße 1, 4531 Kematen / Krems

Tel.: +43 7228 200 880
 E-Mail: office@acs.at

Technische Änderungen und Druckfehler vorbehalten
 Technical changes and printing errors reserved

Produktabbildungen sind Symbolfotos
 Product images are symbolic photos

Copyright© ACS Handels GmbH

Energiekabel 1kV

Power Cables copper 1 kV



Prod. Nr.	Option	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.	Power Load Earth (A)	Power Load Air (A)	Calorific potential (kWh/m)
Prod. Nr.	Option	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.	Power Load Earth (A)	Power Load Air (A)	Calorific potential (kWh/m)
01302103	J	3 x 25/16 rm/re	black - black	1.363,0	22,5	133	106	2,22
01302097	J	3 x 35 sm	black - black	1.231,0	22,5	159	129	2,47
01302105	J	3 x 35/16 sm/re	black - black	1.416,0	23,9	159	129	2,53
01302098	J	3 x 50 sm	black - black	1.688,0	25,9	188	157	2,60

ACS Handels GmbH
Kabel - Leitungen - Zubehör
 Bahnhofstraße 1, 4531 Kematen / Krems

Tel.: +43 7228 200 880
 E-Mail: office@acs.at

Technische Änderungen und Druckfehler vorbehalten
 Technical changes and printing errors reserved

Produktabbildungen sind Symbolfotos
 Product images are symbolic photos

Copyright© ACS Handels GmbH

Energiekabel 1kV

Power Cables copper 1 kV



Prod. Nr.	Option	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.	Power Load Earth (A)	Power Load Air (A)	Calorific potential (kWh/m)
Prod. Nr.	Option	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.	Power Load Earth (A)	Power Load Air (A)	Calorific potential (kWh/m)
01302107	J	3 x 50/25 sm/rm	black - black	1.977,0	28,2	188	157	2,78
01302099	J	3 x 70 sm	black - black	2.450,0	29,5	232	199	3,08
01302109	J	3 x 70/35 sm	black - black	2.642,0	31,6	232	199	4,06
01302100	J	3 x 95 sm	black - black	3.210,0	33,0	280	246	4,06
01302110	J	3 x 95/50 sm	black - black	3.621,0	35,8	280	246	5,19
01302101	J	3 x 120 sm	black - black	4.050,0	36,0	318	285	4,47
01302111	J	3 x 120/70 sm	black - black	4.511,0	39,0	318	285	5,81
01302102	J	3 x 150 sm	black - black	4.870,0	40,3	359	326	5,42
01302112	J	3 x 150/70 sm	black - black	5.466,0	43,0	359	326	7,03
01302182	J	3 x 185 sm	black - black	6.200,0	44,0	406	374	7,03
01302113	J	3 x 185/95 sm	black - black	6.717,0	47,5	406	374	7,55
01302176	J	3 x 240 sm	black - black	8.000,0	52,0	473	445	8,32
01302114	J	3 x 240/120 sm	black - black	8.832,0	53,0	473	445	
01302115	J	3 x 300/150 sm	black - black	11.500,0	65,0	535	511	
01302116	J	4 x 1,5 re	black - black	168,0	10,3	27	20	
01302118	J	4 x 2,5 re	black - black	222,0	11,1	36	25	
01302120	J	4 x 4 re	black - black	336,0	13,4	47	34	
01302121	J	4 x 6 re	black - black	427,0	14,6	59	43	
01302123	J	4 x 10 re	black - black	642,0	16,9	79	59	1,67
01302124	J	4 x 10 rm	black - black	667,0	17,9	79	59	1,67

ACS Handels GmbH
Kabel - Leitungen - Zubehör
 Bahnhofstraße 1, 4531 Kematen / Krems

Tel.: +43 7228 200 880
 E-Mail: office@acs.at

Technische Änderungen und Druckfehler vorbehalten
 Technical changes and printing errors reserved

Produktabbildungen sind Symbolfotos
 Product images are symbolic photos

Copyright© ACS Handels GmbH

Energiekabel 1kV

Power Cables copper 1 kV



Prod. Nr.	Option	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.	Power Load Earth (A)	Power Load Air (A)	Calorific potential (kWh/m)
Prod. Nr.	Option	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.	Power Load Earth (A)	Power Load Air (A)	Calorific potential (kWh/m)
01302125	J	4 x 16 re	black - black	919,0	19,9	102	79	2,03
01302126	J	4 x 16 rm	black - black	958,0	20,4	102	79	2,03
01302127	J	4 x 25 rm	black - black	1.486,0	24,8	133	106	2,61
01302128	J	4 x 35 sm	black - black	1.685,0	25,0	159	129	2,89

ACS Handels GmbH
Kabel - Leitungen - Zubehör
 Bahnhofstraße 1, 4531 Kematen / Krems

Tel.: +43 7228 200 880
 E-Mail: office@acs.at

Technische Änderungen und Druckfehler vorbehalten
 Technical changes and printing errors reserved

Produktabbildungen sind Symbolfotos
 Product images are symbolic photos

Copyright© ACS Handels GmbH

Energiekabel 1kV

Power Cables copper 1 kV



Prod. Nr.	Option	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.	Power Load Earth (A)	Power Load Air (A)	Calorific potential (kWh/m)
Prod. Nr.	Option	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.	Power Load Earth (A)	Power Load Air (A)	Calorific potential (kWh/m)
01302129	J	4 x 50 sm	black - black	2.230,0	29,3	188	157	3,31
01302130	J	4 x 70 sm	black - black	2.999,0	35,0	232	199	4,08
01302131	J	4 x 95 sm	black - black	4.145,0	38,0	280	246	5,11
01302132	J	4 x 120 sm	black - black	5.054,0	40,3	318	285	5,69
01302196	J	4 x 150 sm	black - black	6.280,0	45,0	359	326	6,97
01302134	J	4 x 185 sm	black - black	7.656,0	49,0	406	374	7,50
01302135	J	4 x 240 sm	black - black	10.172,0	58,0	473	445	10,70
01302136	J	5 x 1,5 re	black - black	199,0	10,9	27	20	0,94
01302138	J	5 x 2,5 re	black - black	250,0	11,9	36	25	1,08
01302139	J	5 x 4 re	black - black	395,0	14,3	47	34	1,44
01302140	J	5 x 6 re	black - black	497,0	15,6	59	43	1,64
01302142	J	5 x 10 rm	black - black	821,0	19,8	79	59	2,00
01302143	J	5 x 16 re	black - black	1.103,0	21,8	102	79	2,39
01302144	J	5 x 16 rm	black - black	1.103,0	22,7	102	79	2,39
01302145	J	5 x 25 rm	black - black	1.803,0	28,3	133	106	3,42
01302146	J	5 x 35 rm	black - black	2.331,0	31,5	159	129	
01302147	J	5 x 50 rm	black - black	3.200,0	36,5	188	157	
01302198	J	5 x 70 rm	black - black	4.419,0	41,0	232	199	
01302199	J	5 x 95 rm	black - black	5.385,0	51,0	280	246	
01302200	J	5 x 120 rm	black - black	6.780,0	51,0	318	285	

ACS Handels GmbH
Kabel - Leitungen - Zubehör
 Bahnhofstraße 1, 4531 Kematen / Krems

Tel.: +43 7228 200 880
 E-Mail: office@acs.at

Technische Änderungen und Druckfehler vorbehalten
 Technical changes and printing errors reserved

Produktabbildungen sind Symbolfotos
 Product images are symbolic photos

Copyright© ACS Handels GmbH

Energiekabel 1kV

Power Cables copper 1 kV



Prod. Nr.	Option	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.	Power Load Earth (A)	Power Load Air (A)	Calorific potential (kWh/m)
Prod. Nr.	Option	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.	Power Load Earth (A)	Power Load Air (A)	Calorific potential (kWh/m)
01302219	J	5 x 150 rm	black - black	8.586,0	59,0	359	326	
01302237	J	5 x 185 rm	black - black	11.048,0	63,0	406	374	
01302148	J	7 x 1,5 re	black - black	244,0	11,8	27	20	1,08
01302158	J	7 x 2,5 re	black - black	358,0	14,1	36	25	1,22

ACS Handels GmbH
Kabel - Leitungen - Zubehör
 Bahnhofstraße 1, 4531 Kematen / Krems

Tel.: +43 7228 200 880
 E-Mail: office@acs.at

Technische Änderungen und Druckfehler vorbehalten
 Technical changes and printing errors reserved

Produktabbildungen sind Symbolfotos
 Product images are symbolic photos

Copyright© ACS Handels GmbH

Energiekabel 1kV

Power Cables copper 1 kV



Prod. Nr.	Option	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.	Power Load Earth (A)	Power Load Air (A)	Calorific potential (kWh/m)
01302165	J	7 x 4 re	black - black	566,0	18,0	47	34	
01302167	J	7 x 6 re	grey - grey	681,0	20,0	59	43	
01302150	J	10 x 1,5 re	black - black	367,0	14,2	27	20	
01302160	J	10 x 2,5 re	black - black	517,0	17,3	36	25	
01302155	J	16 x 1,5 re	black - black	506,0	17,5	27	20	
01302163	J	16 x 2,5 re	black - black	750,0	20,1	36	25	
01302220	J	25 x 2,5 re	black - black	1.052,0	24,0	36	25	
01302172	J	48 x 1,5 re	black - black	1.316,0	28,4	27	20	

ACS Handels GmbH
Kabel - Leitungen - Zubehör
 Bahnhofstraße 1, 4531 Kematen / Krems

Tel.: +43 7228 200 880
 E-Mail: office@acs.at

Technische Änderungen und Druckfehler vorbehalten
 Technical changes and printing errors reserved

Produktabbildungen sind Symbolfotos
 Product images are symbolic photos

Copyright© ACS Handels GmbH