

## YSLCY-OZ EB



### Application

For hazardous areas the cables with special marking (blue) (hazard type-i-) used as flexible control and measuring cables to meet the requirements for the installation of electrical apparatus. These installations are not earthed and require a separate power circuit. Those cables are not suitable for underground laying.

The materials used are free from silicon and cadmium and free from varnish damaging substances.

Capacity:  
core / core : appr. 150 nF/km and core / screen : app. 200 nF/km

Inductivity: approx. 0,65 mH/km

### Standards

acc. to DIN VDE 0245, 0285-525-2-31, 0293-308, 0295, IEC 60079-14 Abschnitt 12.2.2 (VDE 0165 Teil 1)

CE = The product is conformed with the EC Low-Voltage Directive 2014/35/EU.

### Construction

<b>Inner Conductor</b>	fine-stranded bare copper acc. DIN VDE 0295 cl. 5 / IEC 60228 cl. 5
<b>Core Insulation</b>	polyvinylchlorid compound (PVC)
<b>Core Color</b>	black cores with continuous white numbers printed
<b>Stranding Elements</b>	cores stranded in layers with optimal laylength
<b>Shielding</b>	Kupfergeflecht, verzinkt
<b>Overall Shielding</b>	braid shield copper tinned
<b>Outer Insulation Material</b>	polyvinylchlorid compound (PVC)
<b>Constant Against</b>	extensively oil resistant

### Application

For hazardous areas the cables with special marking (blue) (hazard type-i-) used as flexible control and measuring cables to meet the requirements for the installation of electrical apparatus. These installations are not earthed and require a separate power circuit. Those cables are not suitable for underground laying.

The materials used are free from silicon and cadmium and free from varnish damaging substances.

Capacity:  
core / core : appr. 150 nF/km and core / screen : app. 200 nF/km

Inductivity: approx. 0,65 mH/km

### Standards

acc. to DIN VDE 0245, 0285-525-2-31, 0293-308, 0295, IEC 60079-14 Abschnitt 12.2.2 (VDE 0165 Teil 1)

CE = The product is conformed with the EC Low-Voltage Directive 2014/35/EU.

### Construction

<b>Inner Conductor</b>	fine-stranded bare copper acc. DIN VDE 0295 cl. 5 / IEC 60228 cl. 5
<b>Core Insulation</b>	polyvinylchlorid compound (PVC)
<b>Core Color</b>	black cores with continuous white numbers printed
<b>Stranding Elements</b>	cores stranded in layers with optimal laylength
<b>Shielding</b>	Kupfergeflecht, verzinkt
<b>Overall Shielding</b>	braid shield copper tinned
<b>Outer Insulation Material</b>	polyvinylchlorid compound (PVC)
<b>Constant Against</b>	extensively oil resistant

## Technical Data

<b>Nominal Voltage</b>	U <sub>0</sub> /U: 300 /500 V
<b>Nominal Volatage DC</b>	U <sub>0</sub> /U: 0 /0
<b>Test Voltage</b>	3000 V
<b>Bending Radius moved (xD)</b>	10
<b>Bending Radius fixed (xD)</b>	5
<b>Operating Temperature solid</b>	-40 °C bis 80 °C
<b>Operating Temperature moving</b>	-5 °C bis 80 °C
<b>Fire Classes</b>	Eca

## Technical Data

<b>Nominal Voltage</b>	U <sub>0</sub> /U: 300 /500 V
<b>Nominal Volatage DC</b>	U <sub>0</sub> /U: 0 /0
<b>Test Voltage</b>	3000 V
<b>Bending Radius moved (xD)</b>	10
<b>Bending Radius fixed (xD)</b>	5
<b>Operating Temperature solid</b>	-40 °C to 80 °C
<b>Operating Temperature moving</b>	-5 °C to 80 °C
<b>Fire Classes</b>	Eca

Prod. Nr.	Option	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.
Prod. Nr.	Option	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.
00913050	OZ	2 x 0,5	blue (similar RAL 5015) - blue (similar RAL 5015)	36,0	5,6
00913005	OZ	2 x 0,75	blue (similar RAL 5015) - blue (similar RAL 5015)	56,0	6,7
00913019	OZ	2 x 1	blue (similar RAL 5015) - blue (similar RAL 5015)	65,0	6,4
00913013	OZ	2 x 1,5	blue (similar RAL 5015) - blue (similar RAL 5015)	97,0	8,5
00913006	OZ	3 x 0,75	blue (similar RAL 5015) - blue (similar RAL 5015)	70,0	7,0
00913021	OZ	3 x 1	blue (similar RAL 5015) - blue (similar RAL 5015)	81,0	6,5
00913014	OZ	3 x 1,5	blue (similar RAL 5015) - blue (similar RAL 5015)	125,0	8,9
00913035	OZ	3 x 2,5	blue (similar RAL 5015) - blue (similar RAL 5015)	150,0	9,4
00913007	OZ	4 x 0,75	blue (similar RAL 5015) - blue (similar RAL 5015)	95,0	7,6
00913028	OZ	4 x 1	blue (similar RAL 5015) - blue (similar RAL 5015)	98,0	7,1
00913015	OZ	4 x 1,5	blue (similar RAL 5015) - blue (similar RAL 5015)	165,0	9,7
00913008	OZ	5 x 0,75	blue (similar RAL 5015) - blue (similar RAL 5015)	130,0	8,2
00913022	OZ	5 x 1	blue (similar RAL 5015) - blue (similar RAL 5015)	127,0	7,6
00913016	OZ	5 x 1,5	blue (similar RAL 5015) - blue (similar RAL 5015)	193,0	10,7
00913009	OZ	7 x 0,75	blue (similar RAL 5015) - blue (similar RAL 5015)	168,0	9,5
00913029	OZ	7 x 1	blue (similar RAL 5015) - blue (similar RAL 5015)	158,0	9,1
00913017	OZ	7 x 1,5	blue (similar RAL 5015) - blue (similar RAL 5015)	245,0	11,5
00913026	OZ	8 x 0,75	blue (similar RAL 5015) - blue (similar RAL 5015)	145,0	9,4
00913010	OZ	12 x 0,75	blue (similar RAL 5015) - blue (similar RAL 5015)	232,0	12,0
00913031	OZ	12 x 1	blue (similar RAL 5015) - blue (similar RAL 5015)	260,0	11,2
00913020	OZ	12 x 1,5	blue (similar RAL 5015) - blue (similar RAL 5015)	354,0	16,2
00913024	OZ	18 x 0,75	blue (similar RAL 5015) - blue (similar RAL 5015)	292,0	12,4
00913025	OZ	18 x 1	blue (similar RAL 5015) - blue (similar RAL 5015)	380,0	13,2
00913027	OZ	18 x 1,5	blue (similar RAL 5015) - blue (similar RAL 5015)	479,0	15,2

Prod. Nr.	Option	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.
Prod. Nr.	Option	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.
00913012	OZ	25 x 0,75	blue (similar RAL 5015) - blue (similar RAL 5015)	415,0	15,3
00913030	OZ	25 x 1	blue (similar RAL 5015) - blue (similar RAL 5015)	534,0	16,2
00913018	OZ	25 x 1,5	blue (similar RAL 5015) - blue (similar RAL 5015)	734,0	20,3
00913046	OZ	30 x 0,75	blue (similar RAL 5015) - blue (similar RAL 5015)	486,0	15,8
00913032	OZ	34 x 0,75	blue (similar RAL 5015) - blue (similar RAL 5015)	523,0	16,9
00913023	OZ	34 x 1	blue (similar RAL 5015) - blue (similar RAL 5015)	741,0	20,0
00913049	OZ	34 x 1,5	blue (similar RAL 5015) - blue (similar RAL 5015)	900,0	20,8
00913048	OZ	41 x 0,75	blue (similar RAL 5015) - blue (similar RAL 5015)	680,0	18,6