

(N)HXH-J E30



Application

Security cables are ideal for use everywhere, where in case of fire human life and material assets are to be protected and safety consciousness take a special significance. The cables are suitable for fixed installation in dry and moist rooms, in, above, on and beneath plaster as well as in masonry walls in concrete. These cables are suitable for outdoor applications and in underground by using in conduits or tubes. For installation conduit all precautions must be taken that no accumulation of water can occur in the pipes.

The cables are halogen-free, have low smoke gas development, no fire propagation and insulation retention in the event of fire of 180 minutes in accordance with VDE 0472 Part 814. In addition, the cable has been tested for functional integrity in accordance with DIN 4102 Part 12 (E 30) for all standard carrying systems (Cable troughs and ladders, ceiling installation) and is therefore suitable for use in fire alarm systems, systems for alarming and issuing instructions to people, safety lighting and other backup lighting in accordance with VDE 0108.

Standards

security cable in the case of fire to DIN VDE 0266 & FE 180:
Insulation integrity to DIN VDE 0472 part 814 & E 30:
Function-
ality to DIN 4102 part 12

CE = The product is conformed with the EC Low-Voltage Directive 2014/35/EU.

Construction

- Inner Conductor** bare copper conductor to DIN VDE 0295 cl. 1 or cl. 2, HD 383
- Core Insulation** halogen-free polymer compound
- Core Color** to DIN VDE 0293-308
- Stranding Elements** cores stranded in layers
- Outer Insulation Material** halogen-free polymer compound

Application

Security cables are ideal for use everywhere, where in case of fire human life and material assets are to be protected and safety consciousness take a special significance. The cables are suitable for fixed installation in dry and moist rooms, in, above, on and beneath plaster as well as in masonry walls in concrete. These cables are suitable for outdoor applications and in underground by using in conduits or tubes. For installation conduit all precautions must be taken that no accumulation of water can occur in the pipes.

The cables are halogen-free, have low smoke gas development, no fire propagation and insulation retention in the event of fire of 180 minutes in accordance with VDE 0472 Part 814. In addition, the cable has been tested for functional integrity in accordance with DIN 4102 Part 12 (E 30) for all standard carrying systems (Cable troughs and ladders, ceiling installation) and is therefore suitable for use in fire alarm systems, systems for alarming and issuing instructions to people, safety lighting and other backup lighting in accordance with VDE 0108.

Standards

security cable in the case of fire to DIN VDE 0266 & FE 180:
Insulation integrity to DIN VDE 0472 part 814 & E 30:
Function-
ality to DIN 4102 part 12

CE = The product is conformed with the EC Low-Voltage Directive 2014/35/EU.

Construction

- Inner Conductor** bare copper conductor to DIN VDE 0295 cl. 1 or cl. 2, HD 383
- Core Insulation** halogen-free polymer compound
- Core Color** to DIN VDE 0293-308
- Stranding Elements** cores stranded in layers
- Outer Insulation Material** halogen-free polymer compound



Technical Data

Nominal Voltage	U_0/U : 600 /1000 V
Nominal Volatage DC	U_0/U : 0 /0
Test Voltage	4000 V
Bending Radius fixed (xD)	0
Operating Temperature solid	-5 °C bis 70 °C
Operating Temperature moving	0 °C bis 0 °C

Technical Data

Nominal Voltage	U_0/U : 600 /1000 V
Nominal Volatage DC	U_0/U : 0 /0
Test Voltage	4000 V
Bending Radius fixed (xD)	0
Operating Temperature solid	-5 °C to 70 °C
Operating Temperature moving	0 °C to 0 °C

Kabel und Leitungen E30/E90

Halogen-Free Cables E30 / E90



Prod. Nr. Prod. Nr.	Option Option	Dimensions Dimensions	Color Color	Weight (kg/km) Weight (kg/km)	Outer-Diameter (mm) Outer-Diameter (mm)	Calorific potential (kWh/m) Calorific potential (kWh/m)
02404008	O	1 x 16 re	narancssárga - orange	215.0	9.5	0.34
02404009	O	1 x 25 rm	narancssárga - orange	305.0	11.0	0.39
02404010	O	1 x 35 rm	narancssárga - orange	400.0	12.0	0.45
02404011	O	1 x 50 rm	narancssárga - orange	540.0	13.5	0.53
02404012	O	1 x 70 rm	narancssárga - orange	750.0	15.5	0.66
02404013	O	1 x 95 rm	narancssárga - orange	1,015.0	17.5	0.79
02404084	J	1 x 120 rm	narancssárga - orange	1,255.0	19.0	0.91
02404014	O	1 x 120 rm	narancssárga - orange	1,255.0	19.0	0.91
02404015	O	1 x 150 rm	narancssárga - orange	1,545.0	21.0	1.12
02404016	O	1 x 185 rm	narancssárga - orange	1,925.0	23.0	1.34
02404017	O	1 x 240 rm	narancssárga - orange	2,450.0	26.0	1.61
02404018	O	2 x 1,5re	narancssárga - orange	125.0	9.5	0.34
02404019	O	2 x 2,5re	narancssárga - orange	160.0	10.0	0.40
02404020	O	2 x 4re	narancssárga - orange	210.0	11.0	0.47
02404021	O	2 x 6re	narancssárga - orange	280.0	12.5	0.59
02404022	O	2 x 10 re	narancssárga - orange	420.0	15.0	0.81
02404075	O	2 x 16 rm	narancssárga - orange	630.0	18.5	1.14
02404093	J	3 x 1,5re	narancssárga - orange	145.0	10.0	0.37
02404094	J	3 x 2,5re	narancssárga - orange	190.0	10.5	0.44
02404096	J	3 x 4re	narancssárga - orange	260.0	12.0	0.55
02404095	J	3 x 6re	narancssárga - orange	340.0	13.5	0.65
02404023	J	3 x 10 re	narancssárga - orange	525.0	16.0	0.93
02404109	J	3 x 16 rm	narancssárga - orange	785.0	19.5	1.24
02404025	J	3 x 25 rm	narancssárga - orange	1,140.0	23.0	1.60

Prod. Nr. Prod. Nr.	Option Option	Dimensions Dimensions	Color Color	Weight (kg/km) Weight (kg/km)	Outer-Diameter (mm) Outer-Diameter (mm)	Calorific potential (kWh/m) Calorific potential (kWh/m)
02404030	J	3 x 25/16 rm	narancssárga - orange	1,315.0	24.0	1.74
02404026	J	3 x 35 rm	narancssárga - orange	1,485.0	25.0	1.88
02404031	J	3 x 35/16 rm	narancssárga - orange	1,640.0	26.0	1.99
02404027	J	3 x 50 rm	narancssárga - orange	1,970.0	28.0	2.25
02404032	J	3 x 50/25 rm	narancssárga - orange	2,230.0	30.0	2.46
02404028	J	3 x 70 rm	narancssárga - orange	2,735.0	32.0	2.90
02404033	J	3 x 70/35 rm	narancssárga - orange	3,070.0	34.0	3.12
02404034	J	3 x 95/50 rm	narancssárga - orange	4,180.0	39.0	3.95
02404035	J	3 x 120/70 rm	narancssárga - orange	5,280.0	43.0	4.80
02404036	J	3 x 150/70 rm	narancssárga - orange	6,260.0	47.0	5.61
02404037	J	3 x 185/95 rm	narancssárga - orange	7,925.0	52.0	6.99
02404038	J	3 x 240/120 rm	narancssárga - orange	10,030.0	58.0	8.49
02404099	J	4 x 1,5re	narancssárga - orange	170.0	11.0	0.43
02404089	J	4 x 2,5re	narancssárga - orange	225.0	11.5	0.51
02404040	J	4 x 4re	narancssárga - orange	315.0	13.0	0.64
02404041	J	4 x 6re	narancssárga - orange	435.0	15.0	0.82
02404042	J	4 x 10 re	narancssárga - orange	665.0	17.5	1.16
02404091	J	4 x 16 rm		995.0	22.0	1.50
02404044	J	4 x 25 rm	narancssárga - orange	1,430.0	25.0	1.88
02404045	J	4 x 35 rm	narancssárga - orange	1,680.0	28.0	2.20
02404046	J	4 x 50 rm	narancssárga - orange	2,505.0	31.0	2.73
02404047	J	4 x 70 rm	narancssárga - orange	3,480.0	36.0	3.50
02404048	J	4 x 95 rm	narancssárga - orange	4,705.0	41.0	4.33
02404049	J	4 x 120 rm	narancssárga - orange	5,850.0	45.0	5.25

Prod. Nr. Prod. Nr.	Option Option	Dimensions Dimensions	Color Color	Weight (kg/km) Weight (kg/km)	Outer-Diameter (mm) Outer-Diameter (mm)	Calorific potential (kWh/m) Calorific potential (kWh/m)
02404050	J	4 x 150 rm	narancssárga - orange	7,160.0	49.0	6.35
02404078	J	4 x 240 rm	narancssárga - orange	11,380.0	62.0	9.62
02404102	J	5 x 1,5re	narancssárga - orange	200.0	11.5	0.50
02404103	J	5 x 2,5re	narancssárga - orange	270.0	12.5	0.62
02404053	J	5 x 4re	narancssárga - orange	380.0	14.0	0.77
02404105	J	5 x 6re	narancssárga - orange	520.0	16.0	0.98
02404055	J	5 x 10 re	narancssárga - orange	810.0	19.5	1.39
02404056	J	5 x 16 re	narancssárga - orange	1,300.0	24.0	
02404057	J	5 x 25 rm	narancssárga - orange	1,725.0	27.0	2.21
02404083	J	5 x 35 rm	narancssárga - orange	2,270.0	30.0	2.64
02404085	J	5 x 50 rm	narancssárga - orange	3,075.0	34.0	3.35
02404088	J	5 x 70 rm	narancssárga - orange	4,315.0	40.0	4.37
02404086	J	5 x 95 rm	narancssárga - orange	5,815.0	45.0	5.41
02404004	J	7 x 1,5re	narancssárga - orange	250.0	12.5	0.59
02404064	J	7 x 2,5re	narancssárga - orange	340.0	14.0	0.72
02404071	J	7 x 4 re	narancssárga - orange	485.0	15.5	0.99
02404058	J	10 x 1,5re	narancssárga - orange	370.0	16.0	0.88
02404065	J	10 x 2,5re	narancssárga - orange	505.0	18.0	1.07
02404059	J	12 x 1,5re	narancssárga - orange	415.0	16.5	0.96
02404066	J	12 x 2,5re	narancssárga - orange	565.0	18.5	1.16
02404061	J	19 x 1,5re	narancssárga - orange	600.0	19.5	1.37
02404068	J	19 x 2,5re	narancssárga - orange	830.0	22.0	1.67
02404062	J	24 x 1,5re	narancssárga - orange	760.0	23.0	1.76
02404063	J	30 x 1,5re	narancssárga - orange	940.0	25.0	2.14