

LSZ-XY



Anwendung

Als Verbindungsleitung in Lautsprecheranlagen.

Die verwendeten Materialien bei der Fertigung sind silikon- und cadmiumfrei und frei von lackbenetzungsstörenden Substanzen.

Normen

nach Werksnorm,
selbstverlöschend und flammwidrig EN 60332-1-2, IEC 60332-1

Aufbau

Innenleiter Kupferleiter blank, feindrähtig nach DIN VDE 0295 Kl. 5 / IEC 60228 Kl. 5

Aderisolierung Polyvinylchlorid (PVC)

Verseilelement Adern parallel

Techn. Daten

Nennspannung	U_0/U : 200 /300 V
Nennspannung Gleichstrom DC	U_0/U : 0 /0
Prüfspannung	2000 V
Biegeradius fest (xD)	0
Betriebstemperatur fest	0 °C bis 0 °C
Betriebstemperatur beweglich	-5 °C bis 70 °C

Application

As connecting cable in speaker systems.

The materials used are free from silicon and cadmium and free from varnish damaging substances.

Standards

acc. to factory standard,
self-extinguishing and flame retardant acc. to DIN EN 60332-1-2, IEC 60332-1

Construction

Inner Conductor bare copper fine wire, or extrafine wire
acc. to DIN VDE 0295

Core Insulation special polyvinylchlorid compound (PVC)

Stranding Elements cores parallel

Technical Data

Nominal Voltage	U_0/U : 200 /300 V
Nominal Voltage DC	U_0/U : 0 /0
Test Voltage	2000 V
Bending Radius fixed (xD)	0
Operating Temperature solid	0 °C to 0 °C
Operating Temperature moving	-5 °C to 70 °C

Art. Nr. Prod. Nr.	Option Option	Abmessung Dimensions	Farbe Color	Gewicht (kg/km) ca. Weight (kg/km) approx.	Außen-Durchmesser (mm) ca. Outer-Diameter (mm) approx.
00307034		2 x 0,35	schwarz/rot - black/red	18,0	
00307025		2 x 0,5	schwarz/rot - black/red	22,0	
00307024		2 x 0,5	transparent - transparent	22,0	
00307001		2 x 0,75	schwarz/rot - black/red	26,0	
00307002		2 x 0,75	transparent - transparent	26,0	
00307013		2 x 1	schwarz/gelb - black/yellow	34,0	
00307010		2 x 1,5	schwarz/blau - black/blue	41,0	
00307020		2 x 1,5	transp/rot - transparent/red	41,0	
00307011		2 x 2,5	schwarz/rot - black/red	60,0	
00307005		2 x 2,5	transp/rot - transparent/red	60,0	
00307026		2 x 2,5	schwarz/gelb - black/yellow	60,0	
00307012		2 x 4	schwarz/rot - black/red	80,0	
00307031		2 x 4	transparent - transparent	80,0	
00307008	HF	2 x 10	transparent - transparent	250,0	
00307017		2 x 10	transparent - transparent	250,0	