

YSLCY-JB



Anwendung

Bei mittlerer mechanischer Beanspruchung für flexible Anwendung bei freier Bewegung ohne Zugbeanspruchung und ohne zwangsweise Bewegungsführung in trockenen, feuchten und nassen Räumen, jedoch nicht im Freien, als Steuerleitung in der Steuer- und Regeltechnik, im Werkzeug- und Maschinenbau, in Rechenanlagen, in der Heiz- und Klimatechnik, im Anlagenbau sowie als Signalleitung in der Elektronik. Statt aufwendigem PVC-Innenmantel wird eine stabilisierende Trennfolie zwischen Aderverband und Geflecht eingesetzt. Sie reduziert den Außendurchmesser wesentlich, was geringere Biegeradien, geringeres Gewicht etc. mit sich bringt. Durch die hohe Abschirmdichte wird eine störfreie Übertragung von Signalen bzw. Impulsen sichergestellt. Die ideale störgeschützte Steuerleitung für obige Einsatzzwecke.

Die verwendeten Materialien bei der Fertigung sind silikon- und cadmiumfrei und frei von lackbenetzungsstörenden Substanzen.

Normen

in Anlehnung an DIN VDE 0245, 0285-525-2-31

CE = Das Produkt ist konform zur EG-Niederspannungsrichtlinie 2014/35/EU.

Aufbau

Innenleiter	Kupferleiter blank, feindrähtig nach DIN VDE 0295 Kl. 5 / IEC 60228 Kl. 5
Aderisolierung	Polyvinylchlorid (PVC)
Aderfarbcode	färbig nach HD 308 S2
Verseilelement	Adern mit optimalen Schlaglängen in Lagen verseilt
Gesamtschirmung	Kupfergeflecht, verzinkt
Außenmantelmaterial	Polyvinylchlorid (PVC)
Beständig gegen	weitgehend ölbeständig

Application

For use as a data cable in control circuits, in tool-making and machine industries as well as a signal cable in computer systems and electronics. The more usual PVC inner sheath has been replaced in these cables by a stabilising foil separator, thus reducing the total diameter of the cables considerably and thereby reducing the bending radius, total weight etc. The high covering percentage of the copper screening offers interference-free signal transfer etc. The dense screening assures disturbance-free transmission of all signals and im- pulses. An ideal disturbance-free control cable for the above application.

The materials used are free from silicon and cadmium and free from varnish damaging sustances.

Standards

adapted to DIN VDE 0245, 0285-525-2-31, self-extinguishing and flame retardant acc. to VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1

CE = The product is conformed with the EC Low-Voltage Directive 2014/35/EU.

Construction

Inner	fine-stranded bare copper acc. DIN VDE 0295
Conductor	cl. 5 / IEC 60228 cl. 5
Core Insulation	polyvinyl chloride (PVC)
Core Color	acc. to HD 308 S2
Stranding Elements	cores stranded in layers with optimal lay-length
Overall Shielding	braid shield copper tinned
Outer Insulation Material	polyvinyl chloride (PVC)
Constant Against	extensively oil resistant

Techn. Daten

Nennspannung	U ₀ /U: 300 /500 V
Nennspannung Gleichstrom DC	U ₀ /U: 0 /0
Prüfspannung	2500 V
Biegeradius bew. (xD)	20
Biegeradius fest (xD)	10
Betriebstemperatur fest	-30 °C bis 70 °C
Betriebstemperatur beweglich	-5 °C bis 70 °C
Brandklassen	Eca

Technical Data

Nominal Voltage	U ₀ /U: 300 /500 V
Nominal Volatage DC	U ₀ /U: 0 /0
Test Voltage	2500 V
Bending Radius moved (xD)	20
Bending Radius fixed (xD)	10
Operating Temperature solid	-30 °C to 70 °C
Operating Temperature moving	-5 °C to 70 °C
Fire Classes	Eca

Art. Nr. Prod. Nr.	Option Option	Abmessung Dimensions	Farbe Color	Gewicht (kg/km) ca. Weight (kg/km) approx.	Außen-Durchmesser (mm) ca. Outer-Diameter (mm) approx.
00904205	JB	3 x 0,5	grau - grey	55.0	6.0
00904060	JB	3 x 1,5	grau - grey	122.0	8.0
00904062	JB	3 x 2,5	grau - grey	150.0	9.4
00904212	JB	3 x 4	grau - grey	240.0	11.5
00904228	JB	4 x 0,75	grau - grey	77.0	7.0
00904061	JB	4 x 1,5	grau - grey	126.0	8.7
00904130	JB	4 x 4	grau - grey	310.0	12.7
00904118	JB	4 x 10	grau - grey	783.0	18.5
00904155	JB	4 x 25	grau - grey	1,480.0	25.6
00904168	JB	5 x 1,5	grau - grey	193.0	9.6
00904169	JB	5 x 2,5	grau - grey	223.0	11.3