

LSZ-XY

prihláška

Ako spojovacia linka v reproduktorových systémoch.

Materiály používané pri výrobe neobsahujú silikón a kadmia a neobsahujú látky, ktoré narúšajú zmáčanie farby.

štandardy

podľa výrobných noriem,
samohasiaci a spomaľovač horenia EN 60332-1-2, IEC
60332-1

nastavenia

vnútorný vodič Holý medený vodič, jemne vláknový v súlade
s DIN
VDE 0295 trieda 5/IEC 60228 trieda 5

izolácia jadra polyvinylchlorid (PVC)

Vnútorný prvok Paralelné jadrá

Techn. dáta

| | |
|--------------------------------------|-------------------------------|
| menovité napätie | U ₀ /U: 200 /300 V |
| Menovité napätie DC DC | U ₀ /U: 0 /0 |
| Skúšobné napätie | 2000 V |
| Pevný polomer ohybu (xD) | 0 |
| Pevná prevádzková teplota | 0 °C bis 0 °C |
| Prevádzková teplota pohyblivá | -5 °C bis 70 °C |



Application

As connecting cable in speaker systems.

The materials used are free from silicon and cadmium and free from varnish damaging substances.

Standards

acc. to factory standard,
self-extinguishing and flame retardant acc. to DIN EN
60332-1-2, IEC 60332-1

Construction

Inner Conductor bare copper fine wire, or extrafine wire
acc. to DIN VDE 0295

Core Insulation special polyvinylchlorid compound
(PVC)

Stranding Elements cores parallel

Technical Data

| | |
|-------------------------------------|-------------------------------|
| Nominal Voltage | U ₀ /U: 200 /300 V |
| Nominal Volatage DC | U ₀ /U: 0 /0 |
| Test Voltage | 2000 V |
| Bending Radius fixed (xD) | 0 |
| Operating Temperature solid | 0 °C to 0 °C |
| Operating Temperature moving | -5 °C to 70 °C |

| Art. č. Prod. Nr. | voľba Option | rozmer Dimensions | maľovať Color | hmotnosť (kg/km) Weight (kg/km) approx. | Vonkajší priemer (mm) Outer-Diameter (mm) approx. |
|----------------------|-----------------|----------------------|-----------------------------------|--|--|
| 00307034 | | 2 x 0,35 | black/red - black/red | 18,0 | |
| 00307025 | | 2 x 0,5 | black/red - black/red | 22,0 | |
| 00307024 | | 2 x 0,5 | transparentne - transparent | 22,0 | |
| 00307001 | | 2 x 0,75 | black/red - black/red | 26,0 | |
| 00307002 | | 2 x 0,75 | transparentne - transparent | 26,0 | |
| 00307013 | | 2 x 1 | black/yellow - black/yellow | 34,0 | |
| 00307010 | | 2 x 1,5 | čierna/modrá - black/blue | 41,0 | |
| 00307020 | | 2 x 1,5 | transparent/red - transparent/red | 41,0 | |
| 00307011 | | 2 x 2,5 | black/red - black/red | 60,0 | |
| 00307005 | | 2 x 2,5 | transparent/red - transparent/red | 60,0 | |
| 00307026 | | 2 x 2,5 | black/yellow - black/yellow | 60,0 | |
| 00307012 | | 2 x 4 | black/red - black/red | 80,0 | |
| 00307031 | | 2 x 4 | transparentne - transparent | 80,0 | |
| 00307008 | HF | 2 x 10 | transparentne - transparent | 250,0 | |
| 00307017 | | 2 x 10 | transparentne - transparent | 250,0 | |