

YR



Application

In telecommunications equipment and related facilities, especially for connecting stations with the central unit. For laying indoor, outdoor use is limited. As transmission line in power systems not permitted.

The materials used are free from silicon and cadmium and free from varnish damaging substances.

Standards

acc. to factory standard,
fire testing acc. to EN 60332-1-2

CE = The product is conformed with the EC Low-Voltage Directive 2014/35/EU.

Construction

Inner Conductor bare copper conductor, solid 0,8 mm

Core Insulation Polyvinyl chloride (PVC)

Core Color nach Werksnorm

Outer Insulation Material Polyvinyl chloride (PVC)

Technical Data

Nominal Voltage	U_0/U : 0 /100 V
Nominal Volatage DC	U_0/U : 0 /0
Test Voltage	1000 V
Bending Radius fixed (xD)	15
Operating Temperature solid	-30 °C bis 70 °C
Operating Temperature moving	0 °C bis 0 °C
Fire Classes	Eca

Application

In telecommunications equipment and related facilities, especially for connecting stations with the central unit. For laying indoor, outdoor use is limited. As transmission line in power systems not permitted.

The materials used are free from silicon and cadmium and free from varnish damaging substances.

Standards

acc. to factory standard,
fire testing acc. to EN 60332-1-2

CE = The product is conformed with the EC Low-Voltage Directive 2014/35/EU.

Construction

Inner Conductor bare copper conductor, solid 0,8 mm

Core Insulation Polyvinyl chloride (PVC)

Core Color nach Werksnorm

Outer Insulation Material Polyvinyl chloride (PVC)

Technical Data

Nominal Voltage	U_0/U : 0 /100 V
Nominal Volatage DC	U_0/U : 0 /0
Test Voltage	1000 V
Bending Radius fixed (xD)	15
Operating Temperature solid	-30 °C to 70 °C
Operating Temperature moving	0 °C to 0 °C
Fire Classes	Eca



Prod. Nr. Prod. Nr.	Dimensions Dimensions	Color Color	Weight (kg/km) Weight (kg/km)	Outer-Diameter (mm) Outer-Diameter (mm)
02905001	2 x 0,8	biely - white	35.0	4.8
02905002	3 x 0,8	biely - white	40.0	5.0
02905003	4 x 0,8	biely - white	50.0	5.5
02905004	5 x 0,8	biely - white	60.0	5.9
02905005	6 x 0,8	biely - white	70.0	6.4
02905006	10 x 0,8	biely - white	100.0	8.1